



White Glue

It is a polyvinyl acetate based, water based, white colored glue that forms a flexible and stable film layer after drying.

Areas of Use

It is used for coating and bonding of paper, cardboard, fabric and all kinds of wood surfaces (massive, chipboard and MDF).

Specifications

- Saves labor and time.
- Water soluble.
- At the end of drying times, it forms a film which is flexible, strong and looks like frosted glass.
- Economical and long lasting.
- There is no unpleasant smell during application.

Application

Bianca White Glue Application surfaces; solid, free from all kinds of dirt, oil and dust, clean and dry. It can be applied with brush or roller at minimum + 5° C and maximum + 30° C. It is recommended to mix the product before application. Can be used in hot and cold presses. The pressing time of 5-15 minutes at a pressure of 2-5 kg / cm² is sufficient for a good bonding process. This time may vary depending on the type of wood and the temperature of the press. Glue can be applied to the surface with brush, roller and automatic machines. The glue should be applied in an amount that overflows the edges of the surface to be applied, overflowing parts should be wiped with a damp cloth immediately. Up to 10 minutes after application, bonding should be performed. The lid of the package should be tightly closed after use.

Thinning (Volume)

Ready to use.

Coverage

It is 200-400 gr / m² according to the type, absorbency, structure and film thickness of the surface to be applied.

Storage

Shelf life of the product is 1 years in its original can with the lid unopened.

Packing

1,00 / 3,00 / 20,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.