

TECHNICAL DATA SHEET
Document No: TDS.SYS.008

Revision Date / No: 01.10.2020 / 00



BF-9 Acrylic Wet Area Waterproofing

It is an elastromeric resin-based, solvent-free, single component, waterproofing material.

Areas of Use

- In wet areas such as bathrooms showers toilets,
- · On terraces and balconies.
- Suitable for indoor and outdoor use in kitchens and similar wet spaces.

Specifications

- Bianca BF-9 Acrylic Wet Space Waterproofing is absolutely waterproof.
- Its application is very simple and it has semi-fluid properties. Therefore, it can easily cover even very difficult surfaces.
- · It is elastic.
- Provides excellent adhesion to all kinds of building materials.
- · Maintains its elasticity in hot and cold differences.
- Resistant to weak chemicals and U.V rays.
- It is resistant to mechanical impacts and abrasion.
- It is decorative. It is produced in white.

Application

Surfaces to be applied with BF-9 Acrylic Wet Space Waterproofing; It must be sound, free from any dirt, oil and dust. BF-9 Acrylic Wet Space Waterproofing should be applied at temperatures between + 5 ° C and + 35 ° C, especially in dry weather. For floor preparation, Bianca Insulation Primer is applied and allowed to dry for 4 hours. BF-9 Acrylic Wet Space Waterproofing is applied with a roller or brush in two layers after mixing thoroughly. A minimum of 4 hours must be waited before applying the second coat.

Thinning (Volume)

Use the mixture you have prepared without diluting it.

Drying Period (at 20°C, %65 HR)

Waiting Between Floors: 4 hours

Touch Dry: 4 hours

Complete Drying: 24 Hours

Coverage

It is 1 kg / m² in two layers application, depending on the application type and floor.

Storage

It is 2 years in its unopened original package at room temperature.

Packing

3,50 / 10,00 / 18,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not empty the excess paint into sink or closed.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.