

TECHNICAL DATA SHEET
Document No: TDS.SU.085

Revision Date / No: 01.10.2018 / 00



Artistico - Betoon (Concrete Look Colored Plaster)

It is an acrylic emulsion based, decorative ready-made colored plaster that can be used indoors and outdoors, with a gross concrete appearance.

Areas of Use

It is used with a suitable primer after the preparation of the floor on mineral surfaces such as walls, concrete, drywall, cement board, inside and outside of the buildings.

Specifications

- Thanks to its high water vapor permeability, it allows the steam to be expelled and the surface to breathe.
- It is water resistant.
- It does not have an irritating odor during application.
- · Gives a concrete effect.

Application

After cleaning all kinds of dirt, oil and dust on the surfaces where Bianca Artistico Betoon will be applied, the surface defects should be corrected with Bianca Interior Putty and primed with 2 coats of Bianca Universal Primer. Bianca Artistico Betoon product is mixed with a low-speed mixer, after the primer is completely dry, the first coat is applied with a trowel or steel trowel to a thickness of at least 1 mm. At least 6 hours after the first layer application, the second layer is applied. If different patterns are desired, the surface is given an effect with a special sponge or comb before the 2nd layer dries completely. Then the surface is glazed with a steel trowel to obtain a smooth finish. Care should be taken to keep the ambient temperature at the lowest + 5 ° C and the highest + 35 ° C during the application and for the next 24 hours.

Thinning (Volume)

The product is ready for use. It does not require dilution.

Drying Period (at 20°C, %65 HR)

Dryness to the Touch: 2 - 3 hours Complete Dryness: 24 hours

Coverage

Depending on the surface smoothness, absorbency and application techniques, an area of 1.00 - 1.35 m² is covered with 1 kg for a single layer application.

Storage

The product can be stored for 2 years in its unopened package in a cool place, and protected against direct sunlight and frost.

Packing

25,00 kg

Health, Safety and Environment

- · While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not empty the excess paint into sink or closed.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.