



Artistico – Travertino

(Travertine and Natural Stone Textured Coating)

It is a mineral-based, decorative interior plaster that provides the appearance of travertine on the facades where it is applied.

Areas of Use

It is used on walls, plaster, gross concrete and wooden surfaces in the interior of the buildings with the appropriate primer after the floor preparation.

Specifications

- Thanks to its high water vapor permeability, it allows the steam to be expelled and the surface to breathe.
- Its color does not fade, does not crack, swell or shed.
- It does not have an irritating odor during application.
- It has a perfect covering.

Application

After cleaning all kinds of dirt, oil and dust on the surfaces where **Bianca Travertino** will be applied, the surface defects should be corrected with Bianca Interior Putty and primed with Bianca Vals Primer. **Bianca Travertino** product is applied without dilution, with a steel trowel, with the first coat at least 1 mm thick. At least 6 hours after the first layer application, the second layer is applied. Before the 2nd layer dries completely, an effect is given to the surface with a special sponge or comb. Then the surface is glazed with a steel trowel to obtain a smooth finish. Care should be taken to keep the ambient temperature at the lowest + 5 ° C and the highest + 35 ° C during the application and for the next 24 hours.

Thinning (Volume)

The product is ready for use. It does not require dilution.

Drying Period (at 20°C, %65 HR)

Dryness to the Touch: 2 – 3 hours
Complete Dryness: 48 hours

Coverage

Depending on the surface smoothness, absorbency and application techniques, an area of 1.00 - 1.35 m² is covered with 1 kg for a single layer application.

Storage

The product can be stored for 2 years in its unopened package in a cool place, and protected against direct sunlight and frost.

Packing

3,50 / 20,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not empty the excess paint into sink or closed.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.