

TECHNICAL DATA SHEET
Document No: TDS.SL.059

Revision Date / No: 19.04.2021 / 02



# **Ceramica - Ceramic Paint**

It is an acrylic, solvent based, single component, chemical and physical resistant paint that can be easily applied to surfaces such as tiles, ceramics, marble, granite, concrete.

# Areas of Use

It can be applied to bathroom, kitchen, balcony, terrace ceramics, all kinds of tiles, marble, granite, procelain, glass mosaic, concrete.

# **Specification**

- · Single component and easy to apply.
- Abrasive U.V. rays resistant.
- · High adherence to difficult surfaces.
- · Resistant to water and steam formed in wet areas.

# Application

Remove clumps, protrusions, etc. that spoil the smoothness on the application surfaces. Surfaces to be applied; It must be solid, free from all dirt, oil and dust, clean and dry. It should be applied in two coats for best performance. Wait 24 hours between coats. After the 2-coat painting process is completed, it should not be used for 1 day and should not be contacted with water for 3 days and should be used carefully. It will become resistant to chemicals after 7 days.

Care should be taken to keep the surface and ambient temperature between +5°C and +30°C during the application.

# Thinning (Volume)

It is ready to use. If necessary, up to 5% cellulosic thinner can be added. Stir well before use.

## Drying Period (20°C)

Drying Hard: 3 hours

# Coverage

With 1 liter, 5 - 6 m<sup>2</sup> area is painted for a single layer depending on the application method and the floor.

#### Flash Point

38°C

## Storage

Shelf life is 2 years when stored unopened, dry and cool conditions.

#### **Packing**

0,75 / 2,50 It

# Hazard Classification

- Asp. Toxicity 1, H304: Fatal if enters airways and swallowed.
- Skin Irritation 2 H315: Causes skin irritation.
- BHOT Repeated Exposure 2, H373: May cause damage to organs through prolonged or repeated exposure.
- Reproductive System 2. H361: Suspected of damaging fertility or the unborn child.
- Aquatic Chronic 2, H411: Toxic to aquatic life with long-lasting effects.

# **Precautionary Statements**

## -Precautions

P201: Read special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P264: Wash thoroughly with soap and water after handling.

Orkim Ortaklar Boya Sanayi ve Pazarlama A.Ş. Karaağaç Mah. Hadımköy İstanbul Caddesi No: 36 Büyükçekmece - İstanbul Tel: +90 (212) 858 16 00 (pbx) Faks: +90 (212) 858 04 08 www.biancaboya.com info@biancaboya.com



TECHNICAL DATA SHEET
Document No: TDS.SL.059

Revision Date / No: 19.04.2021 / 02

P273: Avoid release to the environment.

P280: Wear protective gloves / protective clothing / eye protection / face protection.

P281: Use Personal Protective Equipment.

#### -Intervention

P301+P310: IF SWALLOWED: Immediately call the National POISON CENTER at Phone No: 114 or a doctor

P302+352: IF ON SKIN: Wash with plenty of water/... [As modified by IV ATP] P308+P313: IF exposed or under effect: obtain medical attention / treatment.

P321: Specific treatment is required (see the label)

P331: DO NOT induce vomiting.

P332+P313: If skin irritation occurs: Get medical advice / attention. P362: Take off and wash prior to use any contaminated clothing.

P391: Collect spillage.

# -Storage

P403+235: Store in a well ventilated place. Keep cool.

P405: Store locked up.

#### -Disposal

P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste." Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

# Warning Word

Danger

# **Hazard Signs**





