



Line Textured Acrylic Coating

It is an acrylic-based, silicon-added, water-resistant and breathable performance enhanced, patternable, colorful and ready-to-use exterior thermal insulation system coating.

Areas of Use

Acrylic Line Textured Coating is an acrylic based line textured coating that is used to renew on fine and rough plaster, concrete, aerated concrete or self-supporting silicate or acrylic based old paints.

Specifications

- Acrylic Line Textured Coating has high water resistance.
- Its application is very simple and it has semi-fluid properties. Therefore, it can easily cover even very difficult surfaces.
- It is elastic.
- Provides excellent adhesion to all kinds of building materials, high adherence.
- Maintains its elasticity in hot and cold differences.
- Provides respiration on surfaces.

Application

Surfaces to be applied Acrylic Line Textured Coating; It must be sound, free from any dirt, oil and dust. The Acrylic Line Textured Coating is applied to the surface properly with a steel trowel or an appropriate spraying machine at temperatures between + 5°C and + 35°C, especially in dry weather, and excess material is removed from the surface to obtain a particle-thick layer in the product.

After the Acrylic Line Textured Coating is applied homogeneously on the application surface, a pattern should be given. In order to obtain a fine line texture, a plastic or polyurethane trowel is pressed and the stones are moved in circular movements and the pattern is given. The hand tools used affect the pattern to be given. In order to avoid pattern differences, the same surfaces should be worked with the same trowel. Trowel surface should be scraped frequently while patterning.

Thinning (Volume)

Ready to use, use without thinning. Mix well before use.

Drying Period (at 20°C, %65 HR)

Final Dry: 24 hours
Complete drying: 2 - 3 days

Coverage

2,5 kg / m² depending on the surface smoothness, absorbency and application techniques.

Storage

It is 2 years in its unopened original package at room temperature.

Packing

25,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not empty the excess paint into sink or closed.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.