



Line Textured Decorative Coating

It is a cement-based, fiber-reinforced, top coat interior and exterior coating that gives a natural texture to the applied surfaces.

Areas of Use

Line Textured Coating is a cement-based line textured coating that is used to renew on fine and coarse plaster, concrete, aerated concrete or self-supporting silicate or acrylic-based old paints.

Specification

- High resistance to water.
- It prevents moisture accumulation.
- It is elastic.
- Provides excellent adhesion to all kinds of building materials, high adherence.
- Its application is very simple and very light. Therefore, even very difficult surfaces can be patterned easily.
- It is resistant to hot and cold differences.
- Provides respiration on surfaces.

Preparation of Mortar

Line Pattern Decorative Coating is mixed with a low speed mixer for about 10 minutes by slowly adding clean and cold water into it until the mixture becomes homogeneous. The required amount of water should be adjusted according to the weather conditions. The mixed mortar is rested for 5 minutes and mixed again. If necessary, the consistency of the mixture is adjusted by adding water. Mixing can also be done with suitable mortar machines and applied to the surface by spraying method. While mixing with the machine, care should be taken that the particles in the product are not eroded. Equal amount of water should be used for each batch of mortar mix. Otherwise, pattern and tone differences may occur on the surface. The prepared mixture should be consumed within 2 hours depending on the weather conditions.

Application

Line Textured Decorative Coating, application surfaces; It must be sound, free from any dirt, oil and dust. Especially in dry weather, it is applied to the surface at temperatures between + 5°C and + 35°C with a steel trowel or a suitable spraying machine and the excess material is removed from the surface to obtain a particle-thick layer in the product. In applications to be made on the old painted surface, it should be checked that the old paint adherence is complete.

After the Line Textured Coating application is applied homogeneously on the surface, the pattern should be given. In order to obtain a fine line texture, a plastic or polyurethane trowel is pressed and patterned with up-down or right-left movements. The hand tools used affect the pattern to be given. In order to avoid pattern differences, the same surfaces should be worked with the same trowel. While patterning, the trowel surface should be scraped frequently.

Thinning (Volume)

25,00 kg Line Textured Decorative Coating is mixed with 6 - 6,5 lt of water. The application may vary depending on the weather conditions.

Drying Period (at 20°C, %65 HR)

Final Dry: 24 hours
Complete drying: 2 - 3 days

Coverage

Dry product consumption 3 - 3,5 kg / m² (it should be taken into consideration that it may differ depending on the surface and application conditions).

Storage

It is 2 years in its unopened original package at room temperature.

Packing

25,00 kg Kraft bags

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not empty the excess paint into sink or closed.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.