



## Foresta Water Based Wood Paint

Acrylic copolymer emulsion based, ready to use, water based wood paint.

### Areas of Use

It is used in wooden door-window joinery, on all kinds of wooden surfaces except horizontal wooden floors and surfaces with pedestrian traffic.

### Specifications

- It is used to give a wooden pattern to exterior coating materials.
- With its UV resistant colors, it provides extraordinary protection against the harmful effects of UV rays present in sunlight.
- Resistant to atmospheric conditions and pollution, sunlight, friction and impacts.
- Thanks to its elastic structure, it does not break or crack.
- It does not have an irritating odor during application.

### Application

Surfaces on which Bianca Foresta Water Based Wood Paint will be applied; It should be clean and dry, free from all kinds of dirt, oil and dust, old paint residues. The roughness on the surface should be cleaned. Cracks should be repaired with repair mortar. During the application, care should be taken that the surface and ambient temperature is between + 5°C minimum and + 30°C at most. After the surface preparation is completed, priming with Bianca Decorative Exterior Primer will increase adherence and provide significant economy in paint consumption. After 6 hours, Bianca Foresta Water Based Wood Paint is applied. It is applied with a brush or roller in a single coat so that it penetrates the surface completely and evenly. In order to prevent fluctuation on large surfaces, the material should always be diluted with the same amount of water, mixed well and applied on the surface without a break. There should be no excessive wind and air flow in the application environment.

### Thinning (Volume)

It is ready to use.

### Drying Period (at 20°C, %65 HR)

First Drying Time: 15 minutes

Second Layer Application: 2 hours

Final Dry: 24 hours

### Coverage

With 1 liter, 8 - 12 m<sup>2</sup> area is painted in one layer, depending on the application and the floor.

### Storage

It is 2 years in its unopened original package at room temperature.

### Packing

0,75 / 2,50 / 15,00 lt

### Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not empty the excess paint into sink or closed.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.