



## Nirvana Pure Acrylic Exterior Paint

It is a silky matte, top coat exterior paint with pure acrylic, silicon modified, high color strength and excellent water repellency.

### Areas of Use

It can be applied on acrylic and mineral based plasters, concrete, exposed concrete, betopan, old painted, terracite type surfaces.

### Specifications

- Resistant to atmospheric conditions and pollution, sun rays, friction and impacts.
- With its hydrophobic feature, it releases the moisture formed on the surfaces.
- Provides high UV resistance with its silicone modified pure acrylic binder system.
- It does not lose its color and brightness for many years, does not crack, swell or shed.
- Easy to apply thanks to the high spreading power on the surface, saving time and labor.
- Gives matte appearance to the surfaces with its carefully selected colors and high quality.
- It does not have an irritating odor during application.
- It has a perfect covering.

### Application

The surfaces on which Bianca Nirvana Pure Acrylic Exterior Paint will be applied; It should be clean and dry, free from all kinds of dirt, oil and dust, old paint residues. The roughness on the surface should be cleaned by blasting. Cracks should be repaired with acrylic based putty. Bianca Nirvana Pure Acrylic Exterior Primer should be applied before applying Bianca Nirvana Pure Acrylic Exterior Paint. After the primer dries, Bianca Nirvana Pure Acrylic Exterior Paint is applied in two layers with a brush or roller, so that it penetrates the surface completely and evenly. During application, care should be taken that the surface and ambient temperature is between +5°C minimum and +30°C at most. After the surface preparation is completed, Bianca Nirvana Pure Acrylic Exterior Paint is applied with a brush or roller in two coats so that it penetrates the surface completely and evenly. There should be no excessive wind and air flow in the application environment.

### Thinning (Volume)

You diluted 15% with water in both coats. Stir the paint thoroughly before use and do not mix the paint with another brand of paint.

### Drying Period (at 20°C, %65 HR)

First Drying Time: 1 - 2 hours  
Second Layer Application: 6 - 8 hours  
Final Dry: 24 hours

### Coverage

With 1 liter, an area of 10 - 12 m<sup>2</sup> is painted in one layer, depending on the application and the floor.

### Storage

The product can be stored for 2 years in its unopened package in a cool place, and protected against direct sunlight and frost.

### Packing

2,50 / 7,50 / 15,00 lt

### Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not empty the excess paint into sink or closed.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.