



Nirvana Pure Acrylic Exterior Primer

It is a pure acrylic, silicone modified, high adherence exterior primer.

Areas of Use

It can be applied on acrylic and mineral based plasters, concrete, gross concrete, betopan, old painted, terracite type surfaces.

Specifications

- It has high adherence and penetration.
- With its hydrophobic feature, it releases the moisture formed on the surfaces.
- Easy to apply thanks to its high spreading power on the surface, saving time and labor.
- It does not have an irritating odor during application.
- It prevents the paint applied on it from being absorbed by the surface.

Application

The surfaces on which Bianca Nirvana Pure Acrylic Exterior Primer will be applied; It should be clean and dry, free from all kinds of dirt, oil and dust, old paint residues. The roughness on the surface should be cleaned by blasting. Cracks should be repaired with Bianca Exterior Putty. During application, care should be taken that the surface and ambient temperature is between + 5°C minimum and + 30°C at most. After the surface preparation is completed, Bianca Nirvana Pure Acrylic Exterior Primer is applied with a brush or roller in one coat so that it penetrates the surface completely and evenly. There should be no excessive wind and air flow in the application environment.

Thinning (Volume)

You diluted 15% with water in both coats.

Drying Period (at 20°C, %65 HR)

Drying Time: 6 - 8 hours

Coverage

With 1 liter, a single coat of 12 - 14 m² is primed depending on the application and the floor.

Storage

The product can be stored for 2 years in its unopened package in a cool place, and protected against direct sunlight and frost.

Packing

2,50 / 7,50 / 15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not empty the excess paint into sink or closed.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.