



Salute - Antibacterial Pure Acrylic Ceiling Plastic

It is a water-based, matte, antibacterial ceiling paint that is resistant to the formation of microorganisms, has minimal allergy potential, pure acrylic, silicone added, high wiping resistance.

Areas of Use

It is used safely in health institutions and medical areas such as hospitals, operating rooms, pharmaceutical factories, schools, nurseries, children's rooms, bathrooms, kitchens, cafeterias, food production facilities, where hygiene is very important. It is applied on interior surfaces, walls and ceilings, old painted surfaces, lime-washed surfaces, plastered, briquette and concrete surfaces.

Specifications

- Prevents the formation of mold and fungus on the applied surfaces. It has a minimum allergy causing feature.
- Thanks to its high breathing ability, it allows ceilings to breathe.
- Has a matte and smooth appearance, does not shine under the light.
- Has a very high covering ability.
- Does not swell and spill.
- It saves time and labor thanks to its high spreading power on the surface during application.
- Does not have an irritating odor during application.

Application

The surfaces on which **Bianca Salute Antibacterial Pure Acrylic Ceiling Plastic** will be applied; It must be strong, free from all kinds of dirt, oil and dust, clean and dry. Old paints should be scraped clean and cracks on the surface should be filled with putty. It is recommended to apply two coats, 4 - 6 hours should be waited between coats. It can be applied with a brush or roller at minimum +5°C, maximum +30°C.

Thinning (Volume)

Thin with water by 25%. Mix the paint well before use and do not mix the paint with another brand of paint.

Drying Period (20°C)

Initial Drying: 15 minutes
Second Coat Application: 4 - 6 hours
Final Drying: 24 hours
It gains its test strength after 7 days.

Coverage

With 1 kilogram, 10 - 12 m² area is painted in one coat, depending on the application method and the floor.

Storage

2 years at room temperature in its unopened original package.

Packing

3,50 / 10,00 / 17,50 kg

Hazard Classification

H314: Causes severe skin burns and eye damage.
H317: May cause an allergic skin reaction.
H411: Toxic to aquatic life with long-lasting effects.

Additional Hazard Information Statements

EUH071 - Corrosive to the respiratory tract.

Precautionary Statements

-Precautions

- P260: Do not breathe dust / fumes / gas / mist / vapours / spray.
P264: Wash ... thoroughly after handling.
P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves / protective clothing / eye protection / face protection.

-Intervention

- P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352: IF ON SKIN: Wash with plenty of water/....
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P310: Immediately call a POISON CENTER/doctor/....
P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.
P363: Wash contaminated clothing before reuse.
P391: Collect spillage.

-Storage

- P405: Store locked up.

-Disposal

- P501: Dispose of contents / container to ...in accordance with local / regional / national / international regulation.

Warning Word

Danger

Hazard Signs

