



Ceramic Top Primer

It is an acrylic emulsion-based primer with high adhesion power applied to increase adherence before the application of ceramic coating on ceramic.

Areas of Use

It is used on ceramic, glassy, mosaic or wooden surfaces to increase adherence or decrease the absorbency of the surface.

Specifications

- Ready to use, easy and fast to apply.
- It is odorless and can be used safely indoors.
- It has high adhesion strength.
- It is applied before cement and gypsum based coatings, preventing rapid water loss of the mortar.
- It has high resistance to moisture.
- It has high water impermeability feature thanks to the special polymers it contains.

Application

- The application surface should be solid, free from all kinds of dirt, oil, dust and frost, and be clean and dry.
- Loose and weak parts on the surface, grout of cement, ponded water, coatings, etc. there should be no foreign matter.
- During application, the ambient temperature should be between + 5°C and + 35°C.
- The surface should be cleaned and conditioned with high pressure water or abrasive equipment.
- Mix with a low-speed mixer for at least 3 minutes in a clean container or in its own package, free of any substance preventing adhesion. Do not add foreign material.
- It is applied to the surface with a brush or roller in one layer. Preliminary testing is recommended for different applications.
- If several coats are to be applied, a minimum of 1 hour between coats and a minimum of 3 hours should be waited for the top coat application.
- It cannot be used alone as a waterproofing material.

Thinning (Volume)

Ready to use, use without thinning. Before use, make sure that it becomes homogeneous by mixing it well.

Drying Period (at 20°C, %65 HR)

First Drying: 1 hour
Second Layer Application: 3 hours
Final Drying: 24 hours

Coverage

With 1 kg, an area of 6 - 8 m² is primed in one layer, depending on the application and the floor.

Storage

The product can be stored for 1 year in its unopened package in a cool place, and protected against direct sunlight and frost.

Packing

1,00 / 3,00 / 12,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not empty the excess paint into sink or closed.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.