



Stella - Water Based Pure Acrylic Paint (Wood and Metal Colors)

It is a new generation paint with excellent adhesion to all surfaces, water-based, pure acrylic-based, wood and metal appearance.

Areas of Use

It can be applied on all kinds of wood, furniture, parquet, laminate, ceramic, tile, marble, glass, plastic, metal, aluminum, galvanized, zinc, porcelain, fabric, wall, stone, paper, cardboard.

Specifications

- Hiding power is very high.
- It has excellent water resistance. Since it has very good water resistance, it also provides waterproofing on the applied surface.
- It has high chemical resistance (soap, cleaning detergent, diluted bleach etc.)
- It has high adhesion strength, does not require any primer.
- It is dirt and stain resistant and can be easily cleaned with a wet and soapy cloth.
- Perfumed, does not have an irritating odor.
- It is suitable for use in all indoor and outdoor spaces.

Application

Stella Wood Appearance Paint Application

Preparation before application: The application surface must be clean. The surface must be free from all factors that will reduce the adhesion of the paint to the surface, such as all dust, dirt, oil. Sub-floor preparation is made on the required pre-prepared surface in 2 coats without diluting Stella Water-Based Pure Acrylic Paint with a silk brush, velvet varnish roller or spraying to obtain a wooden pattern appearance. Wait at least 2 hours between coats.

Application: In order to obtain a wooden appearance on the surface after the preparation of the subfloor with Bianca Stella Pure Acrylic Paint, pour the required amount of Stella Wood Appearance Paint into an empty container and add water at the same rate and mix until it becomes homogeneous. Always apply in one direction and as a single layer, always staying on the same plane with the help of a shortcut brush or sponge.

Stella Metal Appearance Paint Application

The application surface must be clean. The surface should be free of all factors that will reduce the adhesion of the paint to the surface, such as all dust, dirt, oil and silicone, and sanding should be done when necessary. It does not require any primer before application. It is recommended to prime the surface with Bianca Antipas to prevent corrosion on metal surfaces. After opening the package of Bianca Stella Metal Appearance Paint, it is mixed until a homogeneous consistency is obtained. The product is applied to the pre-prepared surface in 2 layers, without thinning, with a silk brush, velvet roller or spraying. Between floors min. You should wait 2 hours.

During the application, care should be taken to ensure that the applied surface and ambient temperature are between +5°C and +30°C.

Protection with Liquid Glass

It is recommended to use Stella Water-Based Liquid Glass or Maximo Solvent-Based Liquid Glass for the protection of surfaces such as parquet, laminate, floor tiles, and tables where physical activity is present, 24 hours after the paint application is completed. Maximo Solvent Based Liquid Glass should be used, especially on surfaces such as kitchen countertops.

Thinning (Volume)

Stella Wood Appearance Paint should be diluted with water in a one-to-one ratio.

Stella Metal Appearance Paint is ready to use.

Mix until it becomes homogeneous before application.

Drying Period (20°C)

Touch Drying: 1 - 2 hours. **Final drying:** 24 hours. Application surfaces should not be used for 1 day, and surfaces exposed to water should not be used for 2 days. Water should not be allowed to accumulate for the first 7 days and should be protected against impacts.

Coverage

Stella Wood Appearance Paint: With 0.25 liter, 8 - 10 m² area can be painted in one coat by thinning it one to one with water, depending on the application method and the floor.

Stella Metal Appearance Paint: With its 0.25 liter, 2 - 3 m² of area can be painted in two coats without thinning, depending on the application method and the floor.

Storage

2 years at room temperature in its unopened original package.

Packing

0,25 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.