



Water Based Varnish

It is a water-repellent, protective wood varnish that is resistant to sunlight, moisture and other atmospheric conditions.

Areas of Use

It is used for decorative and protective purposes on soft and hard, all interior and exterior wooden surfaces, doors, windows, wooden garden furniture and other wooden materials.

Specifications

- Ready to use, easy and fast to apply.
- It is odorless and can be used safely indoors.
- It has high adhesion strength.
- It has high resistance to moisture.
- It has high water impermeability feature thanks to the special polymers it contains.

Application

- The application surface should be solid, free from all kinds of dirt, oil, dust and frost, and be clean and dry.
- Loose and weak parts on the surface, grout of cement, ponded water, coatings, etc. there should be no foreign matter.
- Surface; It should be cleaned and conditioned with high pressure water or abrasive equipment.
- Mix with a low-speed mixer for at least 3 minutes in a clean container or in its own package, free of any substance preventing adhesion. Do not add foreign material.
- It is applied to the surface with a brush or roller in one layer. Preliminary testing is recommended for different applications.
- It cannot be used alone as a waterproofing material.

Thinning (Volume)

It is ready to use.

Drying Period (at 20°C, %65 HR)

Second Layer Application: 8 hours
Hardening Dry: 24 hours

Coverage

With 1 liter, an area of 12 - 14 m² is primed in one coat, depending on the application and the floor.

Storage

The product can be stored for 2 years in its unopened package in a cool place, and protected against direct sunlight and frost.

Packing

2,50 / 7,50 / 15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not empty the excess paint into sink or closed.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.