



Tenta - Roof Insulation Paint (Thermal Roof)

It is an acrylic copolymer based roof insulation paint which provides thermal insulation thanks to the ceramic spherical additive structure.

Areas of Use

Houses, flats, buildings, buildings, commercial buildings, offices, office buildings and factories made of briquette, eternite, concrete carpets, plaster, polystyrene and polyurethane foam, mobile home roofing, gravel roofing, asphalt roofing, concrete roofing, galvanized metal is the known roofing paint used..

Specifications

- It is resistant to ultraviolet rays.
- It has a structure which is resistant to oxidation, salt, moisture and weak chemical solutions.
- The capillary cracks on the wall are not visible due to elasticity.
- Resistant to atmospheric conditions and pollution, sunlight, friction and impacts.
- It does not fade, crack, swollen and flake.
- Easy to apply and saves time and labour thanks to high diffusion on surface.
- It brings an opaque appearance to facades with its specially chosen colours and high quality.
- Does not have a disturbing smell during application.

Application

The surfaces subject to **Bianca Tenta - Roof Insulation Paint** application, must be clean and dry, free from all kinds of dirt, oil and dust, as well as old paint remainders. The temperature of the surface and the surroundings must be min +5°C, Max +30°C. Applied as a single layer either with brush or roller availing the complete and equal penetration of the paint into the surface. Do not mix it with a paint of another trade-mark. Use more paint in areas where there are holes and cracks. Minimum 2 coat application is recommended. There should be no extreme wind or air circulation in the application area.

Thinning (Volume)

Ready to use. If necessary, thin it with water.

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 1 - 1,5 m².

Storage

Shelf life of the product is 1 years in its original can with the lid unopened.

Packing

15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.